



FIRE HOSE





Description

Fireguard produces various types firefighting hoses with high quality for most demanding situations. All hoses are manufactured according to national fire protection association (NFPA)1961 latest edition. The Fireguard Model 150,200,250 & 300 synthetic fire hose is widely used by firefighters worldwide. This hose features: tough durable and abrasion resistant, supplied with different couplings. The all-synthetic construction makes rot proof and easy to clean.

Feature

- High Abrasion to resistance
- Light weight
- Maintenance free
- Easy to clean
- Weather resistance
- Nominal Size 1½" & 2½"

Application


- Fire Departments and Professional Industry services
- Refineries
- Airports
- Oil rigs
- Building Protection

**Standard Lengths: 15,22 & 30 m (50,75 & 100ft)

Construction

polyester filaments in wrap and in weft direction with smooth EPDM lining for low friction loss


Page 1 of 2



EPDM Liner

Polyester Single Jacket Warp: Polyester spun

Weft: Filament polyester



EPDM Liner

Polyster Inner Jacket


Polyester Outer Jacket

Warp: Polyester spun

Weft: Filament polyester

Singel Jacket Hose

Double Jacket Hose



BS336 Coupling in Brass & Aluminuim

MODEL	TYPE	SIZE	TEST PRESSURE-PSI	BRUST PRESSURE-PSI	APPROVAL
FGH150	SINGEL JACKET	1½"	150	450	UL
FGH200	SINGAL JACKET	1½"& 2½"	200	600	UL
FGH15-250	SINGLE JACKET	1½"	250	500	FM
FGH25-250	SINGLE JACKET	2½"	250	500	FM
FGH300	DOUBLE JACKET	1½"& 2½"	300	900	UL